

# CD CHANGER PLAYER Six-Disc

CD-600



## ▶ Features

### ■ Amplifier Section

- \* RCA jack for line L/R Stereo output
- \* RCA jack for recording Stereo output
- \* Music –on hold CD
- \* Designed for operation either AC mains or 24VDC
- \* Rack Mountable Kit

### ■ 6 CD Changer Section

- \* Auto 6 CD Changer Deck Mechanism
- \* Play/Pause Function
- \* Disc Selection Function (D-UP,D-DN )
- \* Track Selection Function (T-UP,T-DN )
- \* Repeat (DISC) Function (RPT)
- \* Pause (DISC) Function (PAUSE)
- \* Scan (DISC) Function (SCAN)
- \* Power On/Off
- \* 6 CD LCD Display

### Technical Specifications

<b>AMPLIFIER</b>		
Rated Output /Impedance	Rec/Line (pre) Output	0dBm (1000mV) 600 ohm Unbalanced
	Music-on hold	0dBm (1000mV) 600 ohm Balanced
Frequency Response		Rec. / Line : Less than -1dB (20Hz ~ 20KHz)
Signal to Noise Ratio		Line : More then 80dB ("A" weight)
T.H.D (at 1KHz Output )		Less than 0.5%
<b>6CD SECTION</b>		
Digital Filter		8 Times over sampling
T.H.D ( 1KHz )		Less than 0.03% (JIS A)
SN Ratio (1KHz)		More than 85 dB (JIS A)
Dynamic Range (1KHz)		20Hz-20kHz (+/-1dB)
CH Separation (1KHz)		Below measurable limit
Frequency Response		20Hz – 20kHz (+/-1dB)
Wow & Flutter		Below measurable limit
Access Time		Long MAX 8 sec, Short MAX 2 sec
<b>GENERAL</b>		
Power Source		110-240VAC 50/60Hz and 24VDC
Weight (kg/lbs)		4.8/10.6
Dimensions (W x H x D) mm/inch		483 x 88 x 350 & 19" x 3.5" x 13.8"

**OFFICE & FACTORY** : 1115-34 Hwagok-Dong, Kangseo-ku, Seoul, Korea.

**www.suhyoon.co.kr E-MAIL:** suhyoon@suhyoon.co.kr