

TALK BACK MOBILE AMPLIFIER

PAT-20TB



Features

- * Protection for product reliability
 - Over current limiter circuit
 - Over heating protection
- * Soft start circuit for power on
- * Control : 1 aux, 1 tone, master volume, talk back, on/off power
- * Input : 1 Mic (PL-55), AUX (RCA)
- * Two-way communication via talk-back control button
- * Plug in cigarette lighter adapter for instant DC power supply
- * Underlying suction cups for secure placement complete with mounting bracket

Technical Specifications

AMPLIFIER		
Rated Output (RMS)		20W
Input Sensitivity /Impedance	Mic	-50dBm (2.45mV) 2Kohm Balanced
	Line	-10dBm (245mV) 200Kohm Balanced
Frequency Response		Mic : Less than -3dB (200Hz ~ 20KHz)
		Aux : Less than -3dB (50Hz ~ 20kHz)
Signal to Noise Ratio		Mic : More than 70dB ("A" weight)
		Aux : More than 80dB ("A" weight)
T.H.D (at 1KHz Output)		Less than 1%
Tone Controls		- 10dB at 100Hz
Output/Impedance	Low IMP	4 or 8 Ohm
Inside Speaker Output power		4 Watt Output
GENERAL		
Power Consumption		30W
Power Source		12VDC
Weight (kg/lbs)		1/2.2
Dimensions (W x H x D) mm/inch		130 x 32 x 110 & 5" x 1.3" x 4.3"

OFFICE & FACTORY : 1115-34 Hwagok-Dong, Kangseo-ku, Seoul, Korea.

www.suhyoon.co.kr **E-MAIL:** suhyoon@suhyoon.co.kr