


# MOBILE AMPLIFIER DECK

PAT-25C



[Zoom](#) |

[Print](#) |

[Leaflet](#) | [Drawing](#) | [Manual](#) |

## Features

### ■ AMPLIFIER SECTION

- \* Protection for product reliability
  - Over current limiter circuit
  - Over heating protection
- \* Tone control
- \* Input : Aux 1 (RCA)
- \* Microphone/tape, control switch
- \* Master volume control

### ■ CASSETTE DECK SECTION

- \* Auto Reverse
- \* Rewind Button
- \* Fast Forward Button
- \* Eject Button

**▶ Technical Specifications**

<b>AMPLIFIER</b>		
Rated Output (RMS)		25W (RMS)
Input Sensitivity / Impedance	Mic	-50dBm (2.45mV) 2Kohm Unbalanced
	Line	-10dBm (245mV) 200Kohm Unbalanced
Frequency Response		Mic : Less than -3dB (200Hz ~ 20KHz)
		Aux : Less than -3dB (35Hz ~ 20KHz)
Signal to Noise Ratio		Mic : More then 70dB ("A" weight)
		Aux : More then 80dB ("A" weight)
T.H.D (at 1KHz Rated Output )		Less than 1%
Tone Controls		- 10dB at 100Hz
Output/Impedance	Low IMP	8 Ohm/14.2V
<b>CASSETTE DECK SECTION</b>		
Tape Speed		4.75cm/sec
Wow and Flutter		Less than 0.35%
Signal to Noise Ratio		Better than 60dB
Frequency Response		100Hz to 6.3KHz
<b>GENERAL</b>		
Power Consumption		35W
Power Source		12VDC
Weight (kg/lbs)		1.2/2.6
Dimensions (W x H x D) mm/inch		200 x 55 x 145 & 7.9" x 2" x 5.7"

**OFFICE & FACTORY** : 1115-34 Hwagok-Dong, Kangseo-ku, Seoul, Korea.

**www.suhyoon.co.kr E-MAIL**: suhyoon@suhyoon.co.kr